

EVOQUE

Security and comfort together with technology



Different accessories in the foot board



Optional hospital painted headboard / footboard



FEATURES

PLATFORM

- Epoxy coated steel tube frame.
- Headboard and footboard easy to assemble without tools.
- Complete with support for accessories in both ends of the bed (IV drip rod, lifting pole, etc.)
- Mattress retainers on both sides. They contribute to the correct positioning of the lying surface.
- Anchor holder for straps at thorax and abdomen surface.
- Hydraulic pumping lift raising system accomplished by bilateral pedal device, shored up by compass mechanism for greater stability and loading capacity up to 230 kg.

COMFORT

- 4 independent and removable polyethylene sections bed of high resistance, easy to clean.
- Sections adjustment accomplished by gas spring.
- Useful surface 100%
- Foot section independent from the leg section, with mechanical joint articulation system, providing greater ergonomics.
- FOWLER position to make patient's stay more comfortable (cardiology, asthma, etc.)
- Hydraulic height adjustment from 450 mm to 765 mm by means of bilateral pedal system placed at both sides of the bed.
- Trendelemburg and reverse trendelemburg (+-16°) by pneumatic activation and synchronized pumping and gas system to allow an automatic positioning (OPTIONAL).
- Cardiac chair position accomplished in a maximum leading time of 12 seconds.
- Security distances among all sections joints and articulations in compliance with Directive CE 93/42/CE to prevent and avoid trapping accidents.
- The FOWLER POSITION is of paramount importance for patients suffering from cardiac and respiratory problems, as this can increase their recovery process in a remarkable way.
- LATERAL RETAINERS to avoid mattress movement.
- Independent Foot plane from the knee plane with mechanical articulation, providing greater ergonomics.
- Centralized braking system and steering facility with castors of diameter Ø 150 mm.
- Low base HI polyurethane storage surface to protect the bed mechanism and facilitate and easy cleaning. High capacity and space to locate and place oxygen bottle with grip holders and rest of patient accessories.
- Protective bumpers: 4 protective bumpers stoppers of Ø100 mm, placed at each side corner, to protect the bed while transportation.

HANDLING

TECHNICAL DATA

External dimensions	2150 x 960 mm
Patient surface	2080 x 870 mm
Height adjustment	450 to 765 mm
Backrest tilting	70°
Legrest tilting	45°
Trendelemburg / Reverse trendelemburg (OPTIONAL)	±16°
Maximum working load	230 kg.
Weight without accessories	165 kg.